

RESPONSIBLE DEWATERING, SUSTAINABLE SOLUTIONS

TMASSIVE FLOW MAXIMUM POWER





ADS LHF 30 PUMP

PRODUCT OVERVIEW

The ADS LHF-30 is a fully automatic self-priming centrifugal pump designed for demanding applications such as WellPoint systems, excavation, and heavy-duty dewatering. It is engine-driven, skid-mounted for mobility, and equipped with a vacuum pump for automatic priming and reliable performance.

MATERIAL OF Construction ADS LHF-30

Impeller: SS304 / SS316 / Bronze

Casing: CI / WCB / SS304 / CD4MCuN

Shaft: SS304 / SS316


Seal: Double (Silicon Carbide / Tungsten Carbide)

Skid: Mild Steel



PARAMETER	SPECIFICATION
ENGINE POWER	32 / 38 / 41 HP (1500 / 1800 / 2000 RPM)
HEAD RANGE	28 / 40 / 50 M
DISCHARGE	400 / 490 / 540 M³/H
SOLIDS HANDLING	20 MM
SUCTION × DELIVERY	150 × 150 MM
FUEL TANK	180 L
MAX TEMP	60 °C
MAX SPEED	2000 RPM
HYDROSTATIC TEST PRESSURE	8.25 BAR

The performance curve below shows Head vs Flow for the ADS LHF-30 pump at 1480, 1800, and 2000 rpm.



02

KEY DESIGN BENEFITS

- Heavy-duty power frame with re-greaseable bearings
- Back pull-out design for easy maintenance
- Stainless steel shaft to minimize deflection
- Abrasion-resistant castings with excellent solids handling
- Dynamically balanced impeller for vibration-free performance
- Factory hydro-tested casing & seals for guaranteed reliability

Construction & Excavation

- Mines & Tunnel Dewatering
- Flood Water Removal
- Heavy Sludge & Slurry
- Pipelines / Sewage / Municipal
- Marine & Stream Diversion



Arihant Dewatering Systems

RESPONSIBLE DEWATERING, SUSTAINABLE SOLUTIONS





Phone:

+91 9818740559

Mail:

Sushant.bansal@arihantdewatering.com Sushantbansal.ads@gmail.com Sales@arihantdewatering.com

Address:

46, Anand Industrial Estate, Mohan Nagar, Ghaziabad 201007 U.P.